

Claims

- 5 1. A method for the determination of the object distance (D) between an opto-electronic sensor (11) working according to the principle of triangulation and a sensed object (13),
- 10 - wherein the sensor (11) has at least one measuring channel between a transmission unit (S1; S) for the emission of electromagnetic sensing rays into the measuring region and a reception unit (E; E1) for the detection of sensing rays reflected and/or remitted from the measuring region;
- 15 - wherein the sensor (11) has at least one additional channel which has a further transmission unit (S2) and/or a further reception unit (E2) in addition to the transmission unit (S1; S) and the reception unit (E; E1); and
- 20 - wherein the received signals of the measuring channel and of the additional channel are jointly evaluated in order to determine the object distance (D).
2. A method in accordance with claim 1, characterized in that the measuring channel and the additional channel are operated jointly, and in particular at least substantially simultaneously, for each object distance (D).
- 25 3. A method in accordance with claim 1, characterized in that only the received signal of the measuring channel is used to determine a distance value, in that a determination is made by means of the

received signal of the additional channel whether the received signals fulfill at least one additional criterion and in that the distance value is used as the measure for the object distance (D) if the additional criterion is fulfilled.

5

4. A method in accordance with claim 1, characterized in that the received signals of both the measuring channel and of the additional channel are used to determine a distance value serving as the measure for the object distance (D).

10

5. A method in accordance with claim 1, characterized in that in the measuring channel and/or in the additional channel the respective intensity distribution of the received signal on the reception unit (E) or on the reception units (E1, E2) is used for the determination of the distance.

15

6. A method in accordance with claim 5, characterized in that the position of a center of the intensity distribution or of a characteristic region of the intensity distribution is used in the measuring channel and/or in the additional channel for the determination of the distance.

20

7. A method in accordance with claim 1, characterized in that a separate transmission unit (S1, S2), and preferably a joint reception unit (E), is respectively used for the measuring channel and the additional channel.

25

8. A method in accordance with claim 7, characterized in that the sensing rays of the measuring channel and of the additional channel are emitted in different directions.

5 9. A method in accordance with claim 8, characterized in that when mutually corresponding characteristic regions of the received signals of the measuring channel and of the additional channel are jointly evaluated, an investigation being made in each case whether they are in particular mutually displaced by an expected amount ($a \cdot \Delta X$).

10 10. A method in accordance with claim 7, characterized in that the sensing rays of the measuring channel and of the additional channel are focused at different distances (d_1, d_2), with the focus preferably being at a near range in one channel and at a far range in the other channel.

15 11. A method in accordance with claim 10, characterized in that when mutually corresponding regions of the received signals of the measuring channel and of the additional channel are jointly evaluated, an investigation being made in each case whether the emitted sensing rays are imaged with different sharpness, in particular with a sharpness differing in accordance with an expected amount.

20 25 12. A method in accordance with claim 1, characterized in that the sensing rays of both the measuring channel and the additional channel are focused.

13. A method in accordance with claim 7, characterized in that the sensing rays of the additional channel are deliberately emitted, in particular in an unfocused, scattered, expanded and/or diffuse manner, such that a spatially expanded sensing zone is emitted into the measuring region, with the sensing zone preferably being emitted into at least a substantial part of the half-space of the sensor (11) on the sensed object side and in particular at least substantially into the whole half-space.
14. A method in accordance with claim 13, characterized in that a difference is formed between the received signals of the measuring channel and of the additional channel on the joint evaluation hereof.
15. A method in accordance with claim 13, characterized in that, on the joint evaluation, the received signal of the additional channel is deducted from the received signal of the measuring channel, in that negative difference values are set to zero and in that a resulting positive difference signal is used for the determination of the distance.
16. A method in accordance with claim 13, characterized in that the intensity of the sensing rays are selected such that the received signal is larger in the additional channel than in the measuring channel in a characteristic region which is caused by an interfering object (15) with a high reflection and/or remittance capability in comparison with the sensed object (13).

17. A method in accordance with claim 1, characterized in that a separate reception unit (E1, E2) and/or a separate optical reception system (FE1, FE2) is respectively used for the measuring channel and the additional channel, with preferably a common transmission unit (S) being used.
18. A method in accordance with claim 17, characterized in that the transmission unit is arranged between the at least two reception units and/or optical reception systems, in that a center of the intensity distribution and the distance of the center from the position of the transmission unit are respectively determined for the received signals, and in that the mean value of the center distances are used as a measure for the object distance.
19. A method in accordance with claim 17, characterized in that the at least two reception units (E1, E2) and/or optical reception systems are arranged at the same side of the transmission unit (S) and the distance (ΔX) between mutually corresponding characteristic regions of the received signals of the measuring channel and of the additional channel are used as a measure for the object distance (D).
20. An apparatus for the determination of the object distance (D) between an opto-electronic sensor (11) working according to the principle of triangulation and a sensed object (13),
- having at least one measuring channel between a transmission unit (S1; S) for the emission of electromagnetic sensing rays

into the measuring region and a reception unit (E; E1) for the detection of sensing rays reflected and/or remitted from the measuring region;

- having at least one additional channel which has a further transmission unit (S2) and/or a further reception unit (E2) in addition to the transmission unit (S1; S) and to the reception unit (E; E1); and
- having an evaluation unit for the joint evaluation of the received signals of the measuring channel and of the additional channel in order to determine the object distance (D).

21. An apparatus in accordance claim 20, characterized in that all transmission units and reception units (S, S1, S2, E, E1, E2) are arranged in a common sensor plane (21) which preferably extends perpendicular to the distance direction corresponding to the shortest distance between the sensor (11) and the sensed object (13).

22. An apparatus in accordance with claim 20, characterized in that the or each transmission unit (S, S1, S2) is provided in the form of an LED or a laser device.

23. An apparatus in accordance with claim 20, characterized in that the or each reception unit (E, E1, E2) is provided in the form of a spatially resolving detector, in particular of a single row or multi-row photodiode array, of a CCD (charge coupled device) or of a PSD (position sensitive device).

24. An apparatus in accordance with claim 20, characterized in that all transmission units and reception units (S, S1, S2, E, E1, E2) are arranged in a common sensor housing (23).
- 5 25. An apparatus in accordance with claim 20, characterized in that it is used to carry out the method in accordance with a preceding claim.

104
106
108
110
112
114
116
118
120
122
124
126
128
130
132
134
136
138
140
142
144
146
148
150
152
154
156
158
160
162
164
166
168
170
172
174
176
178
180
182
184
186
188
190
192
194
196
198
200
202
204
206
208
210
212
214
216
218
220
222
224
226
228
230
232
234
236
238
240
242
244
246
248
250
252
254
256
258
260
262
264
266
268
270
272
274
276
278
280
282
284
286
288
290
292
294
296
298
300
302
304
306
308
310
312
314
316
318
320
322
324
326
328
330
332
334
336
338
340
342
344
346
348
350
352
354
356
358
360
362
364
366
368
370
372
374
376
378
380
382
384
386
388
390
392
394
396
398
400
402
404
406
408
410
412
414
416
418
420
422
424
426
428
430
432
434
436
438
440
442
444
446
448
450
452
454
456
458
460
462
464
466
468
470
472
474
476
478
480
482
484
486
488
490
492
494
496
498
500
502
504
506
508
510
512
514
516
518
520
522
524
526
528
530
532
534
536
538
540
542
544
546
548
550
552
554
556
558
560
562
564
566
568
570
572
574
576
578
580
582
584
586
588
590
592
594
596
598
600
602
604
606
608
610
612
614
616
618
620
622
624
626
628
630
632
634
636
638
640
642
644
646
648
650
652
654
656
658
660
662
664
666
668
670
672
674
676
678
680
682
684
686
688
690
692
694
696
698
700
702
704
706
708
710
712
714
716
718
720
722
724
726
728
730
732
734
736
738
740
742
744
746
748
750
752
754
756
758
760
762
764
766
768
770
772
774
776
778
780
782
784
786
788
790
792
794
796
798
800
802
804
806
808
810
812
814
816
818
820
822
824
826
828
830
832
834
836
838
840
842
844
846
848
850
852
854
856
858
860
862
864
866
868
870
872
874
876
878
880
882
884
886
888
890
892
894
896
898
900
902
904
906
908
910
912
914
916
918
920
922
924
926
928
930
932
934
936
938
940
942
944
946
948
950
952
954
956
958
960
962
964
966
968
970
972
974
976
978
980
982
984
986
988
990
992
994
996
998
1000